



TECHNICAL SHEET NUMBER/ LAST REVIEW: 534/ 240518
ISO CERTIFICATION: 9001:2015 N° CA-1.092. ACCREDITED LABORATORY N° 046/ GA/ SA680A

PRODUCT

AUTOMATIC FEEDING SYSTEM

DESCRIPTION

Electronic feeding system specifically developed for the **optimization of feed** delivery in Aquaculture, reducing hand-feeding labour expenditure. Durable and battery or mains operated, built in UV resistant polypropylene ensuring **maximum robustness**. The **waterproof** hopper, with holding capacity of up to 60 Kg, keeps feed dry. Run by 24 hr fully programmable digital timer.

TECHNICAL PROFILE

Hopper capacities: 10, 20, 40 and 60 Kg. Dimensions: Ø min/med/max= 31,5/27/11 cm (10 Kg); 38,5/31,5/11 cm (20 Kg); 47/38/11 cm (40 Kg); 59/48/11 cm (60 Kg). Height: 36 cm (10 Kg), 46 cm (20 Kg), 67 cm (40 Kg), 84 cm (60 Kg). Pellet size range 0 to 8 mm. **Vibration** feeding bell or conveyor **screw** for feed spreading up to 12 m. Readily available, easily replaced spare parts. 24 hr timer, 12 V/24 V, 230 V; runs up to 3 feeders; expandable control box for up to 10 feeders (optional).

REFERENCE PRICE*

From 385 € depending on configuration

*Quotation excludes taxes and delivery costs

ADDITIONAL INFORMATION

Please contact our Commercial Office at ventas@acuinuga.com for further enquiries.

